

Ref. SFOL150M-10



15" Foldable LCD-TFT Professional Monitor with 70 degrees inclination,



*Designed to be integrated
into a meeting and conference
Boardroom tables*



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules
08551 - Tona - BARCELONA
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24
www.soltec-ep.com

DISPLAY

Panel Technology	Active Matrix Panel
Display Area (mm)	304(H) x 228(V)
Size	15"
Pixel Pitch (mm)	0,296 x 0,296
Screen Aspect	4:3
Native Resolution	1.024 x 768
Viewing Angle UDLR	70°/70°/50°/60°
Contrast ratio	400:1 (Typ)
Brightness cd/m2	450 (Typ)
Colors	16,7 M Colors
Response Time	25ms Ton +Toff
Life Time (hours)	50.000

CONNECTIVITY

Analogue RGB input	1xDB15
Digital Input	1xDVI-D
S-Video Input	1xMiniDin
CVBS Input	1xRCA

ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Supply adapter	12VDC - 5A
LCD Consumption	40W
Energy Management	VESA DPMS

MECHANICAL (mm)

Screen	352,5 x 359,6
On Table Cover plate	392,5 x 399,6
Under Table Housing	352,50 x 359,60 x 147
Tilt	70° tilt adjustment
Weight (Kg)	10

ENVIRONMENTAL CONDITIONS

Operation Temperature	+5° to 45°
Storage Temperature	-20° to 60°
Operation Humidity (%)	20 to 80
Storage Humidity (%)	10 to 90

OTHERS

Security	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	220VAC Power Cord 12VDC Power adaptor Installation Manual

OPTIONS

RS-232 Control	1xDB9
RS-485 Control	2xRJ45 (With Loop)
Touch Screen	Projected Capacitive
Customized Housing	Colors, Metal, Logo...
Glass Protection	3mm with black border

Specifications subject to changes without previous notice