

Ref. SFOL156W-10



## WXGA 15.6" Foldable LCD-TFT Professional Monitor with 70 degrees inclination,



*Designed to be integrated  
into a meeting and conference  
Boardroom tables*



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules  
08551 - Tona - BARCELONA  
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24  
[www.soltec-ep.com](http://www.soltec-ep.com)

### DISPLAY

Panel Technology	Edge LED
Display Area (mm)	344,23(H) x 193,53(V)
Size	15,6"
Pixel Pitch (mm)	0,252 x 0,252
Screen Aspect	16:9
Native Resolution	1.366 x 768
Viewing Angle UDLR	80°/80°/85°/85°
Contrast ratio	500:1 (Typ)
Brightness cd/m2	300 (Typ)
Colors	16,7 M Colors
Response Time	8ms Ton +Toff
Protective Glass	3mm with black border
Life Time (hours)	50.000

### CONNECTIVITY

Analogue RGB input	1xDB15
Digital Input	1xDVI
Plug & Play	VESA DDC2Bi
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

### ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Supply adapter	12VDC - 5A
LCD Consumption	30W
Energy Management	VESA DPMS

### MECHANICAL (mm)

Screen	385 x 318
On Table Cover plate	425 x 358
Under Table Housing	385 x 318 x 147
Tilt	70° tilt adjustment
Weight (Kg)	9

### ENVIRONMENTAL CONDITIONS

Operation Temperature	+0° to 60°
Storage Temperature	-20° to 60°
Operation Humidity (%)	5 to 90
Storage Humidity (%)	5 to 90

### OTHERS

Security	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	220VAC Power Cord 12VDC Power adaptor Installation Manual

### OPTIONS

RS-232 Control	1xDB9
RS-485 Control	2xRJ45 (With Loop)
Touch Screen	Projected Capacitive
CVBS + S-Video Inputs	1xRCA / 1xMiniDIN
Display Port	DP 1.1a
Customized Housing	Colors, Metal, Logo...

Specifications subject to changes without previous notice