

Ref. SFOL173W-10



## Full HD 17.3" Foldable LCD-TFT Professional Monitor with 70 degrees inclination,



*Designed to be integrated  
into a meeting and conference  
Boardroom tables*



C/ Metal·lúrgia, 6 Pol. Industrial Les Goules  
08551 - Tona - BARCELONA  
Tel.: +34 93 881 35 25 Fax: +34 93 881 35 24  
[www.soltec-ep.com](http://www.soltec-ep.com)

### DISPLAY

Panel Technology	S-PVA Technology
Display Area (mm)	381.8(H) x 214.8(V)
Size	17.3"
Pixel Pitch (mm)	0,1989 x 0,1989
Screen Aspect	16:9
Native Resolution	1.920 x 1.080
Viewing Angle UDLR	60°/80°/80°/80°
Contrast ratio	600:1 (Typ)
Brightness cd/m2	400 (Typ)
Colors	16,7 M Colors
Response Time	40ms Ton +Toff
Life Time (hours)	50.000
Plug & Play	VESA DDC2Bi

### CONNECTIVITY

Analogue RGB input	1xDB15
Digital Input	HDMI 1.3a (HDCP) DVI (Via HDMI)
Display Port	DP 1.1a
RS-232 Control	1xDB9
Auto Detection	Yes
No Signal Detected	Standby Mode
Identification	DDC2Bi EDiD v1.3

### ELECTRICAL

Power Supply Input	110/220VAC 50~60Hz
Power Supply adapter	12VDC - 5A

LCD Consumption	30W
Energy Management	VESA DPMS

### MECHANICAL (mm)

Screen	435,5 x 359,6
On Table Cover plate	475,5 x 399,6
Under Table Housing	435,5 x 359,6 x 147
Tilt	70° tilt adjustment
Weight (Kg)	11

### ENVIRONMENTAL CONDITIONS

Operation Temperature	+5° to 45°
Storage Temperature	-20° to 60°
Operation Humidity (%)	20 to 80
Storage Humidity (%)	10 to 90

### OTHERS

Security	CE; RoHS
Plug & Play	VESA DDC2Bi
Accessories	220VAC Power Cord 12VDC Power adaptor Installation Manual

### OPTIONS

RS-232 Control	1xDB9
RS-485 Control	2xRJ45 (With Loop)
Touch Screen	Projected Capacitive
Customized Housing	Colors, Metal, Logo...
Protective Glass	3mm with black border

Specifications subject to changes without previous notice